

# DATASHEET

## RadioLinx<sup>®</sup> Intelligent Cellular Ethernet Gateway for Verizon RLXIC-EV

RadioLinx<sup>®</sup> Intelligent Cellular Ethernet modems for Verizon Wireless' USA network provide wide area wireless connectivity for industrial Ethernet devices.

Use the RLXIC-EV Ethernet Gateway for applications requiring Ethernet connectivity on Verizon Wireless' networks. The RLXIC-EV supports the latest 3G CDMA speeds using EV-DO Rev A technology.

The RLXIC-EV has a compact form factor, low power consumption and is Class I Div 2 certified for hazardous locations. Applications include SCADA for oil & gas, water & wastewater, and electric utility automation; as well as M2M applications such as remote equipment monitoring, management and control



Features	Benefits
Cellular Wide Area Wireless Networking	<ul style="list-style-type: none"> <li>◆ Leverage existing, secure cellular infrastructure and avoid need for expensive antenna &amp; cable installations and / or new antenna towers</li> <li>◆ Licensed frequencies and cellular technology limits interference common to unlicensed bands</li> <li>◆ Utilize cellular network backhaul to bring data from geographically diverse locations through the internet to one or more locations</li> </ul>
ALEOS™ Embedded Intelligence	<ul style="list-style-type: none"> <li>◆ Reliable, persistent network connectivity</li> <li>◆ Real-time device status and health including network connectivity, throughput and signal strength</li> <li>◆ Over-the-air device configuration and firmware updates</li> </ul>
Integrated Industrial Protocol Support	<ul style="list-style-type: none"> <li>◆ Simple integration with industrial Ethernet devices</li> <li>◆ Two digital I/O ports enable exception based communications from remote equipment</li> </ul>
Easy to Configure and Monitor	<ul style="list-style-type: none"> <li>◆ USB port simplifies configuration and troubleshooting</li> <li>◆ AceManager utility for local or over-the-air device configuration or diagnostics</li> <li>◆ Configuration templates may be customized and copied to many devices</li> </ul>
Backed by ProSoft Technology <sup>®</sup>	<ul style="list-style-type: none"> <li>◆ Cellular service provider expertise to assist with selection of the best carrier and service features for your application</li> <li>◆ Industrial data communications experts who understand your protocols, devices and applications</li> <li>◆ Three year standard warranty</li> </ul>

### Configuration

RadioLinx Intelligent Cellular products are configured using the included AceManager device monitoring and configuration tool. AceManager supports remote, over-the-air device configuration and firmware updates. Remote diagnostics include network connectivity, throughput, and signal strength. An enterprise-grade application, AceNet, is available separately and enables one-to-many device configuration, management and logging of performance statistics.

## Specifications

### Radio

Cellular Technology	CDMA EV-DO Rev A with fall back to: <ul style="list-style-type: none"><li>◆ CDMA 1x EV-DO Rev 0</li><li>◆ CDMA 1xRTT</li><li>◆ CDMA IS-95</li></ul>
---------------------	---

Bands	800 MHz cellular 1900 MHz PCS
-------	----------------------------------

Typical Downlink Speeds	Up to 3.1 Mbps <sup>1</sup>
-------------------------	-----------------------------

Typical Uplink Speeds	Up to 1.8 Mbps <sup>1</sup>
-----------------------	-----------------------------

### Dimensions & Interfaces

Size	104 x 76 x 27 mm (L x W x D) 4.1 x 3.0 x 1.1 in
------	--

Weight	160 grams (5.6 oz)
--------	--------------------

Enclosure	Aluminum. DIN-rail mounting clip included
-----------	---

USB	2.0 (Mini-B5)
-----	---------------

Antenna	SMA 50 Ohm
---------	------------

I/O Port	2 digital
----------	-----------

LED Indicators	Network, Signal, Activity, Power
----------------	----------------------------------

Applications Interfaces	TCP/IP, UDP/IP, DHCP, HTTP, SNMP, SMTP, SMS, MSCI, Modbus, DF1 and more
-------------------------	---

### Environmental & Power

Operating Temperature	-30°C to 70°C
-----------------------	---------------

Storage Temperature	-40°C to 85°C
---------------------	---------------

Input Voltage	9 – 28 VDC
---------------	------------

Input Current	110 – 250 mA
---------------	--------------

Idle Current	80 mA @ 12 VDC
--------------	----------------

Transmit/Receive (Typical/Max)	350/450 mA @ 12 VDC
--------------------------------	---------------------

<sup>1</sup> Theoretical peak, actual throughput will depend on available network bandwidth and operating mode.

## Agency Approvals & Certifications

### Wireless Approvals

Visit our web site [www.prosoft-technology.com](http://www.prosoft-technology.com) for current wireless approval information.

### Hazardous Locations

Intertek C22.2 213-M1987	ISA 12.12.01 Class I, Division 2, Groups A, B, C, D
-----------------------------	---



N7N-MC5725



2417C-MC5725

Industry  
Canada

Industrie  
Canada



3056308



## Additional Products

ProSoft Technology® offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

For a complete list of products, visit our web site at:  
[www.prosoft-technology.com](http://www.prosoft-technology.com)

## Ordering Information

To order this product, please use the following:

### RadioLinx® Intelligent Cellular Ethernet Gateway for Verizon

#### RLXIC-EV

##### Kits

N America: RLXIC-EV

*Includes: radio, 2 dBi antenna, Ethernet and USB cable, DIN-rail bracket, CD, and AC power supply*

##### Radio Only

N America: RLXIC-EV-RO

*Includes: radio, DIN-rail bracket and DC power cable*

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to:

[www.prosoft-technology.com](http://www.prosoft-technology.com) and select Distributors from the menu.

Place your order by email or fax to:

North American / Latin American / Asia Pacific  
[orders@prosoft-technology.com](mailto:orders@prosoft-technology.com)  
fax to +1 661.716.5101

Europe / Middle East / Africa  
[europe@prosoft-technology.com](mailto:europe@prosoft-technology.com)  
fax to +33 (0) 5.61.78.40.52

Copyright © 2010 ProSoft Technology, Inc., all rights reserved. February 02, 2010

Specifications subject to change without notice.